

INSTALLATION INSTRUCTIONS

HONDA GOLDWING BALANCERS PART NO. MGW100-102 / MGW100-103

FRONT WHEEL INSTALLATION

STEP 1	Remove wheel from motorcycle
STEP 2	Remove wheel weights, they are no longer necessary
STEP 3	Remove left and right rotors
STEP 4	Clean back of rotor where it contacts the wheel. This should be done with a wire brush
STEP 5	Place balancer on the wheel with the balancer ring facing the wheel
STEP 6	Place rotor on the wheel
STEP 7	Replace new rotor bolts per manufacturers recommendations
STEP 8	Apply thread lock, then re-install bolts
STEP 9	Tighten rotor bolts to manufacturers specifications

REAR WHEEL INSTALLATION

- STEP 1 Remove all 5 lug nuts
- **STEP 2** Remove wheel from hub
- **STEP 3** Remove wheel weights, they are no longer necessary
- **STEP 4** Place rear balancer on the hub with the balancer ring facing the wheel
- **STEP 5** Place the rear wheel back on the hub
- **STEP 6** Replace lug nuts and tighten to manufacturers specifications

THANK YOU FOR CHOOSING CENTRAMATIC!

Pictures are not model specific, and are only shown as a visual aid for some of the steps. They do not show the entire installation process.









For technical support and dealer inquires please contact:

KEYSTONE DISTRIBUTING | 949.268.9005 | 185 AVENIDA LA PATA | SAN CLEMENTE, CA 92673