



## MOUNTING SUGGESTIONS:

### Kawasaki Vulcan 800 1996-2005 One-piece Seat

<b>Hardware:</b>	Stock 6mm rear bolt White nylon washer
<b>Tools needed:</b>	Metric socket and Allen wrenches

#### Removal of stock seat:

1. Remove rear 6mm bolt and set aside. This bolt will be used to mount your new Mustang seat.

2. Slide the seat back and up to remove. **Note: The seat is often very tight, some force may be necessary.**

3. Remove the center bracket from the fender and re-install the two bolts into the fender.



#### Installation of Mustang seat:

1. Engage the front bracket into the frame receptacle under the tank.

2. Position the white nylon washer between the rear bracket and the fender hole and secure the seat with the stock 6mm bolt.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to [questions@mustangseats.com](mailto:questions@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75919, 75930, 75933, 76338

You are cordially invited to  
**— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.