



Rally Phone Mount
Ducati Multistrada V4
MBK.22.10100


Thank you for choosing DENALI
We know you would rather be riding your bike than wrenching on it, so we go the extra mile to make sure our instructions are clear and as easy to understand as possible. If you have any questions, comments, or suggestions don't hesitate to give our gear experts a call at 401.360.2550 or visit WWW.DENALIELECTRONICS.COM

Please Read Before Installing
DENALI products should always be installed by a qualified motorcycle technician. If you are unsure of your ability to properly install a product, please have the product installed by your local motorcycle dealer. DENALI takes no responsibility for damages caused by improper installation. **Caution:** When installing electronics it is extremely important to pay close attention to how wires are routed, especially when mounting products to the front fender, front forks, or fairing of your motorcycle. Always be sure to turn the handlebars fully left, fully right, and fully compress the suspension to ensure the wires will not bind and have enough slack for your motorcycle to operate properly.


Installation Tips
We strongly recommend using medium strength liquid thread locker on all screws, nuts, and bolts. It is also important to ensure that all hardware is tightened to the proper torque specifications as listed in your owner's manual. For included accessory hardware please refer to the default torque specifications provided below. Inspect all hardware after the first 30 miles to ensure proper torque specifications are maintained.

Bolt Size	in-lbs	ft-lbs	Nm
M3	10.0 in-lbs	-	1.0 Nm
M4	23.0 in-lbs	-	2.5 Nm
M5	44.5 in-lbs	3.5 ft-lbs	5.0 Nm
M6	78.0 in-lbs	6.5 ft-lbs	9.0 Nm
M8	-	13.5 ft-lbs	18.0 Nm
M10	-	30.0 ft-lbs	41.0 Nm
M12	-	52.0 ft-lbs	71.0 Nm

Hardware Sizing Guide
Not sure what size bolt you have? Use this ruler to measure screws, bolts, spacers, etc. Remember, the length of a screw or bolt is measured from the start of the "mounting surface" to the end of the screw, so only include the screw head when measuring countersunk screws.



What's In The Box?




Kit Contents

- (a) 12mm Phone Mounting Bar (MBK.22.10100-03).....Qty 1
- (b) Left Hand Side Mounting Bracket (MKB.22.10100-01).....Qty 1
- (c) Right Hand Side Mounting Bracket (MKB.22.10100-02).....Qty 1
- (d) M6x12mm Hex Head Screw.....Qty 1

Tools Required:


- (a) T25 Torx Wrench
- (b) 10mm wrench

1. Installing The Rally Phone Mount



1.1 - Mounting Location

Step One: Remove the windshield by removing the 4x Torx screws. Then, pull outward to remove the windscreen from the rubber dampeners. (We recommend using a microfiber cloth to prevent scratching or smudging on the windshield)



1.2 - Installing the Mount

Step One: Loosely assemble the Rally Phone Mount as shown using the M6x12mm bolts, then install the mount over the top windshield rubber dampeners.

Step Two: Place windshield back on the bike over the rally phone mount and tighten the 4x Torx screws.

Step Three: Adjust the phone mount to your preferences and tighten all the remaining hardware.