



**Fitting Instructions for OCG0026BK Oil Cooler Guard**  
**DUCATI MULTISTRADA 1200 '15-**



**In This Kit There Should Be**  
**1x Oil Cooler Guard (OCG0026BK)**  
**2x 100mm Lengths of self-adhesive Foam**  
**2x Cable Ties**  
**1x Rubber Trim (SRS003)**

**TOOLS REQUIRED**

- Cable cutters
- 4mm Allen key or socket bit & wrench.



Picture 1



Picture 2



Picture 3



Picture 4



Picture 5



Picture 6



Picture 7



Picture 8



Picture 9



Picture 10



Picture 11



Picture 12



Picture 13



Picture 14

### **FITTING INSTRUCTIONS**

- To fit the oil cooler guard to the bike cut the foam strip provided into 10mm wide pieces and stick them to the back of the oil cooler guard frame, so that they sit between the oil cooler guard and the oil cooler radiator.
- Remove the black plastic cover that is positioned in front of the fuel filler cap, as shown in pictures 1 & 2.
- There are two bolts securing the black plastic bodywork on either side that are now visible. Remove these bolts before gently sliding the bodywork on either side of the bike forward to release them from their mounts, as shown in picture 3.
- On the underside of the nose, remove the three bolts that secure the black plastic cover in place, as shown in picture 4, and gently remove by pulling downwards to remove the plastic boss from the rubber mount, as shown in picture 5.
- Remove the two bolts that secure the nose bodywork in place, as arrowed in picture 6. Remove the same bolts on the other side of the bike before gently pulling the nose clear a small distance (*the sensor wiring will limit this*), as shown in picture 7.
- Disconnect the sensor from its mount before removing the nose from the bike, as shown in pictures 8 & 9.
- Remove the rubber mount from the front mount of the oil cooler radiator, as shown in picture 10.
- Take the rubber trim supplied and cut it in half, as shown in picture 11.
- Fit these two pieces to either side of the metal bracket, as shown in picture 12.
- Slide the oil cooler guard into place by locating the lower slot over the lower oil cooler mount and over the two pieces of rubber trim, as shown in picture 13.
- The top mounts should now be located over the top of the oil cooler radiator with the slots for the cable tie positioned on the back edge of the oil cooler radiator, as shown in picture 14. Loop one cable tie through the two slots and around the oil cooler mount before tightening. Repeat this on both sides of the radiator.
- Re-fit the rubber mount to the large hole in the lower radiator mount.
- Ensure the oil cooler guard is correctly mounted before tightening both cable ties.
- The bike can now be re-assembled in the same way that it was dis-assembled.
- Offer the nose up to the bike and re-connected the sensor.
- Re-fit the nose along with the four bolts, before tightening.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



- Offer up the black plastic cover to the underside of the nose, ensuring to correctly locate the plastic boss through the rubber mounts, before re-fitting the three bolts and tightening.
- Re-fit the two black plastic side panels by offering up into place and sliding rearwards to locate the plastic mounts. Once in place, re-fit the two bolts at the top.
- Re-fit the black plastic cover that is positioned in front of the fuel filler cap.
- Ensure all bolts are tight and that the bodywork is correctly mounted and secured.

ISSUE 1 21/07/2015 (AR)

**Digital copies of these instructions are available to download from [www.rg-racing.com](http://www.rg-racing.com)**

#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing  
Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ  
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



**INSTRUCTIONS DE MONTAGE POUR OCG0026BK**  
**Grille de protection du refroidisseur d'huile**  
**DUCATI MULTISTRADA 1200 '15-**



**Le kit doit contenir :**

- 1x Grille de protection (OCG0026BK)
- 2x 100mm Longueurs de mousses autocollantes
- 2x Colliers de serrage
- 1x Garniture en caoutchouc (SRS003)

**OUTILS REQUIS**

- Pince coupante
- Clé Allen 4mm.



Photo 1



Photo 2



Photo 3



Photo 4



Photo 5



Photo 6



Photo 7



Photo 8



Photo 9



Photo 10



Photo 11



Photo 12





Photo 13



Photo 14

### **Instructions de montage :**

- Couper la mousse en bandeaux de 10mm puis collez ces bandeaux au bas du support de refroidisseur d'huile, de façon à ce que ces bandeaux se situent entre la protection refroidisseur d'huile et le refroidisseur d'huile.
- Enlever le cache plastic noir positionné à l'avant du capuchon de remplisseur de carburant, voir photos 1 & 2.
- Il y a 2 boulons qui fixent le carénage noir de chaque coté et qui sont à présent visibles.. Enlever ces boulons avant de glisser doucement le carénage de chaque coté de la moto vers l'avant pour les libérer de leur support, voir photo 3.
- Au bas du nez, enlevez les 2 boulons qui fixent le cache noir en plastic en place, voir photo 4, puis enlever en tirant vers le bas pour enlever le patron en plastic du support en caoutchouc, voir photo 5.
- Enlever les 2 boulons qui fixent le carénage de nez en place, voir photo 6. Enlever les mêmes boulons de l'autre coté de la moto avant de tirer doucement le nez pour libérer une courte distance (les fils de capteur limiteront cette distance), voir photo 7.
- Déconnecter le capteur de son support avant d'enlever le nez de la moto, voir photos 8 & 9.
- Enlever le support en caoutchouc du support avant du radiateur refroidisseur d'huile, voir photo 10.
- Prendre la garniture en caoutchouc fournie et coupez la en 2 moitiés, voir photo 11.
- Positionnez ces 2 moitiés de chaque coté du support en métal, voir photo 12.
- Glissez la grille de protection refroidisseur d'huile en place en plaçant la fente inférieure sur le support inférieur de refroidisseur d'huile et sur les 2 pièces de la garniture, voir photo 13.
- Les supports supérieurs doivent maintenant être placés sur le haut du radiateur refroidisseur d'huile avec les fentes positionnées pour accueillir le collier de serrage, voir photo 14. Encercliez un collier de serrage dans les 2 fentes et autour du support de refroidisseur d'huile avant de serrer. Répétez cette action des 2 cotés du radiateur.
- Remonter le support caoutchouc sur le trou large sur le support inférieur de radiateur.
- Veiller à ce que la protection refroidisseur d'huile soit correctement montée avant de serrer les 2 colliers de serrage.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)



- La moto peut à présent être réassemblée de la même façon qu'elle a été partiellement démontée.
- Montez le nez sur la moto puis reconnecter le capteur.
- Remettre le nez avec les 4 boulons, avant de serrer.
- Monter le cache noir en plastic au dessous du nez, en veillant à placer correctement le patron de plastic dans les supports en caoutchouc, avant de remonter les 3 boulons et de serrer.
- Remonter les 2 carénages plastic noir en les mettant en place et en les glissant vers l'arrière pour placer les supports plastic. Une fois en place, remontez les 2 boulons sur le haut.
- Remonter le cache plastic noir qui est positionnée à l'avant du capuchon de remplisseur de carburant.
- Veiller à ce que tous les boulons soient serrés et que le carénage soit correctement fixé.

ISSUE 1 21/07/2015 (AR)

**Ces instructions de montage sont disponibles en téléchargement sur [www.rg-racing.com](http://www.rg-racing.com)**

#### **CONSUMER NOTICE**

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

#### **R&G RACING RETURNS POLICY (NON-FAULTY GOODS)**

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G Racing

Unit 1, Shelley's Lane, East Worldham, Alton, Hampshire, GU34 3AQ

Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 [www.rg-racing.com](http://www.rg-racing.com) Email: [info@rg-racing.com](mailto:info@rg-racing.com)