

MOUNTING SUGGESTIONS:

Kawasaki Mean Streak '02-08, Suzuki VZ1600 '04 & M95 '05 Solo and Passenger Seat

Hardware: Stock 6mm bolt x 2

Stock fender acorn nut

White nylon washer

Tools needed: 8mm wrench

Removal of stock seat:

 Locate and remove the two 6mm bolts from each side of the seat, and the rear acorn nut from the fender.

2. Slide seat back and up to remove.



Installation of Mustang seat:

- 1. Engage the front bracket of the solo into the frame receptacle under the tank.
- 2. Insert and secure the two 6mm bolts through the seat brackets and into the frame.
- 3. Slide passenger seat's front bracket into the receiver in the back of the solo. Push fully forward until rear

bracket aligns with the fender mount.



4. Secure the rear bracket to the fender with the stock acorn nut.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75850, 75851, 75852, 75853, 75854, 75855, 79290, 79291, 79292, 79293, 79294, 79295

You are cordially invited to Tour the Mustang Factory

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.