



Mounting Suggestions for the Kawasaki Vulcan 1500 Classic 1996-2008 (Carburetor Model Only) One-Piece Seat

- Tools Required:
- Metric Wrenches
 - Metric Sockets

- Hardware:
- Stock 6 mm seat bolts



Baseplate Features:

The one-piece, marine-grade fiberglass baseplate is a direct replacement for the stock two-piece seat. Rubber bumpers are strategically located to protect the frame and fender.

Stock Seat Removal Steps

1. Remove the bolt on each side of the solo.
2. Slide nose of solo forward and up to remove.
3. Remove 6 mm bolt at front of passenger seat.
4. Slide passenger seat forward to release from fender brackets.

Mounting of Mustang Seat

Note: Mustang seat will only mount properly when using the fender bracket farthest to the rear.

1. Slide seat back into rear fender bracket.
2. Push forward to engage nose bracket under the large tank washer.
3. Secure using stock side bolts.

Enjoy the comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to questions@mustangseats.com, or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref part #75949