



Mounting Suggestions Victory Vegas, Kingpin, & 8-Ball 2003-Up Two-Piece Seat

Tools Required:
6 mm Allen Wrench
13mm Socket

Hardware:
Four Hex Head 13 mm x 8 mm Bolts
(Included)

**Note: Mustang Seats will not fit with Tour Pak on Kingpin Tour Models.
Seats will not fit with a luggage rack on the 2012-2013 Vegas models.**

Baseplate Features

Built on a marine-grade fiberglass baseplate, the two-piece seat mounts just like stock. Passenger seat is mounted using the supplied mounting bracket. Rubber bumpers on the solo prevent the seat from touching the frame and fender. Note: Details regarding relocation of Kingpin Luggage rack [click here](#).



Stock Seat Removal Steps

Solo Seat

1. Pull out on side covers to remove. Remove the two solo mounting bolts using a 6 mm Allen wrench (one on each side).
2. Lift solo seat up and off frame. Solo seats do not have a nose bracket.

Passenger Seat

3. Remove four chrome fender strut bolts with a 6 mm Allen wrench (two one each side).
4. Remove four seat bracket bolts from fender (two on each side) with a 6 mm Allen wrench.
5. Lift rear seat up and off fender.



Step 1



Step 2



Step 3



Step 4



Step 5

Mounting of Mustang Seat

Solo Seat

1. Slide front of solo seat into V of gas tank, then lower seat onto frame. Mustang seat has no nose bracket and installs like the stock seat. *NOTE: Mustang solo will not fit with the stock passenger seat.*
2. With the Mustang passenger seat in place, position back of solo on fender first, then bring nose down into V of gas tank. Seats foam fits snug against tank as it's being positioned.
3. Slide solo forward until seat's U-bracket lines up with frame's 8 mm mounting holes. Use 6 mm Allen wrench to tighten.

Passenger Seat

4. Align the Mustang rear seat bracket legs with the four mounting holes in fender.
5. Install the supplied four hex head 8 mm bolts with a 13 mm socket and tighten.
6. Reinstall the chrome fender strut covers with a 6 mm Allen wrench and tighten.



These steps are guidelines to help you install your new Mustang product. If you need further assistance please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit www.mustangseats.com

For care and maintenance of our seats, please go to our website under ["Support"](#).

Ref: Part #76510, 76511, 76512, 76513, 76514, 76515, 79380, 79381, 79382, 79383, 79384, 79385

Enjoy the comfort of your
new Mustang Seat!



Details regarding relocation of Kingpin Luggage rack

Victory Kingpin 2004-2012 ONLY

Luggage rack U-bracket relocation
with Mustang seat.



Drill through the 2 rivets fastening
the the U-bracket to the luggage
rack with a 3/16" bit.



Drill 2 new 1/4" holes through luggage
rack 2-1/4" forward of old holes.



Drill U-bracket legs from 3/16"
holes to 1/4". Install supplied 1/4-
28 allen bolt and lock nut through
one side of rack and bracket.
Bend bracket to reach other side
of rack then install 2nd allen bolt.
Now install luggage rack to back-
rest and U-bracket to the top of
license plate mount.

