



Mounting Suggestions:

Honda VT750 Aero 2004-09 & 2011-up Two-Piece Seat



Baseplate Features:

The two-piece, marine-grade fiberglass baseplate is a direct replacement for the stock seat. Rubber bumpers are strategically placed to prevent the seat from touching the frame and fender.

Removal of stock seat:

1. Locate and remove rear fender screw.
Metric wrench needed.



2. Locate two side mount screws.



3. Remove both side mount screws. Metric Allen wrench needed.



4. Remove stock seat as a one-piece unit by lifting rear end of seat up and pulling whole seat back to disengage the nose tab.



Mounting Suggestions: Honda VT750 Aero 2004-09 & 2011-up Two-Piece Seat

Installation of Mustang Two-Piece Seat:

1. Insert rear seat's front tab into back of front seat.



2. Engage nose tab and align both side tabs of front seat with mounting points on bike frame.



3. Install both side screws; tighten. Metric Allen wrench needed.



4. Install and tighten rear fender screw. Metric wrench needed.

Enjoy the comfort of your new Mustang seat!



These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

Refers to part numbers 76521, 76520, 79390, 79391