



Mounting Suggestions:

Honda VT750 ACE 1998-03

Two-Piece Seat



Baseplate Features:

The marine-grade fiberglass baseplate features rubber bumpers to prevent it from touching the frame and fender. The solo has a single tab that aligns with the fender hole. Passenger seat engages into the solo bolt and attaches in the rear with the stock bolt.

Removal of stock seat:

1. Remove bolt at back of rear seat.
2. Slide rear seat forward and tilt upward to remove it from the bike.
3. Remove the single bolt at the back of the front seat.
4. Slide front seat back to remove it from the bike.

Installation of Mustang Two-Piece seat:

1. Engage nose tab of front seat into frame and install the bolt at the rear of the front seat.
2. Slide the bracket on the front of the rear seat onto the bolt at the back of the front seat.
3. Place plastic washer under rear mounting tab of rear seat.
4. Install and tighten rear fender bolt.

Enjoy the comfort of your
new Mustang seat!



These steps are guidelines to help you install your new Mustang Product. If you need further assistance, please call us at 800-243-1392 or 860-582-9633, Monday through Friday 9:00 – 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

Refers to part numbers 75000, 75001, 79151, 79150