



## Mounting Suggestions Suzuki 800 Volusia 2001-04 & C50 & T 2005-11 Two-Piece Seat

### Tools Required:

- 8 mm Allen Wrench
- 5/8" Deep Socket or Open-End Wrench

### Hardware:

- Stock rear 8 mm Allen Screw
- Triangle Bracket with 1/4"-20 Stud x 1
- Grooved 1/4"-20 Nut x 1



### **Baseplate Features:**

The two-piece, marine-grade fiberglass baseplate is a direct replacement for the stock two-piece seat. Rubber bumpers are positioned to protect the frame and fender.

### **Stock Seat Removal Steps**

1. Remove the rear 8 mm Allen Screw. This screw will be used later to secure your new Mustang Two-Piece Seat.
2. Slide the passenger seat back to remove.
3. Remove rear seat mounting bracket with handstrap.
4. Slide solo back and up to remove.



Step 1



Step 2



### **Mounting of Mustang Seat**

1. Install the special triangle bracket to the fender with stock bolts
2. Engage front of solo into frame below tank. Attach rear of solo to the special triangle bracket and secure with the slotted nut.

*Note: Do not over tighten slotted nut.*

### **Mounting of Mustang Seat cont'd**

3. Slide the slotted bracket on the front of the passenger seat into the slotted nut.
4. Secure seat in rear using stock 8 mm Allen screw.

Step 3



Step 4



**Enjoy the Comfort of  
your new Mustang Seat!**

These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to [questions@mustangseats.com](mailto:questions@mustangseats.com), or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Ref part #75810, 75811, 76060, 76061, 79282, 79283, 79620, 79621