

# INSTALLATION

# CYLINDER BASE COVER

8392

FITS: ALL '07-UP ROAD KINGS, ROAD GLIDE, STREET GLIDE, ELECTRA GLIDE, AND ALL '06-UP DYNA MODELS.

### **PARTS INCLUDED**

- 1 Cylinder Base Cover
- 1 Hot Spot
- 1 5/16"-18 x 3-1/4" Socket Head Cap Screw
- 1 5/16-18 x 4" Socket Head Cap Screw
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

## THANK YOU FOR CHOOSING KÜRYAKYN!

#### **PLEASE NOTE**

It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Küryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

WARNING! YOU WILL BE WORKING AROUND THE ENGINE DURING INSTALLATION ENSURE THAT THE ENGINE HAS FULLY COOLED TO PREVENT INJURY.

# **TOOLS SUGGESTED**

Set of hex wrenches, set of combination wrenches, torque wrench with hex bits/sockets.

## **PROCEDURE**

**STEP 1** Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

**STEP 2** Remove the nut and lock washer on the front of the shift linkage; disconnect the front end of the shift linkage from the shifter lever. Secure the shift linkage up and out of the way during the rest of the installation.


**STEP 3** Remove the stock fastener on the left side of the crankcase as shown in PIC.1.

**STEP 4** Position the Cylinder Base Cover in place and secure it with the included 5/16"-18 x 3-1/4" Socket Head Cap Screw. 96" and 103" engines use the 3-1/4" long screw. 110" engines require the 4" screw. Torque the fastener to 15-19 ft. lbs.

**STEP 5** Push the Hot Spot into the head of the new fastener.

**STEP 6** Reconnect the shift linkage and shift lever; tighten the nut.

**STEP 7** Check for proper clearance before operating the motorcycle.



#### **CUSTOMER SERVICE**

877.370.3604 (toll free)

# INSTALLATION QUESTIONS

techsupport@kuryakyn.com or call 715.247.2983

#### **LIMITED WARRANTY**

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breech of contract or duty between Küryakyn and a customer.
  - Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Küryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

#### **ABOUT OUR CATALOG**

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today-select the "CATALOGS" icon. Each Küryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Küryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.

