



**FITTING INSTRUCTIONS FOR ECC0118 RHS ENGINE CASE COVER
TO FIT DUCATI DIAVEL**



In this kit there should be:

- 1 x Engine Case Cover (ECC0118).
- 2 x M6x40mm long button head bolts.
- 1 x M6x90mm long button head bolt.
- 1 x M6x100mm long button head bolt.

PLEASE READ THESE INSTRUCTIONS FULLY BEFORE STARTING

- Please make sure the engine is cold before proceeding with the fitting of the R&G cover.
- Remove the four engine case bolts arrowed above. Hold the cover loosely over the case to help identify the correct ones.
- Fit the new engine case cover over the original and place the longer bolt (100mm) through the hole marked 'B', the slightly shorter bolt (90mm) through the hole marked 'A', and the shorter bolts (40mm) through the holes marked 'C'.
- With a 4mm Allen key tighten the bolts equally so that they pull the cover into place. DO NOT FULLY TIGHTEN.
- Finally use a torque wrench set at 10 nm (7 Lb ft) to fully tighten.
- It is suggested that you check the tightness of the mounting bolts on a regular basis i.e. when cleaning or once a month.

R&G RACING

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- NOTE for the cleaning of this product you should only use a soft polishing cloth and a mild general cleaning agent.
- AVOID HARMFUL CHEMICALS IF IN DOUBT DO NOT USE AS THEY COULD ALTER THE STRENGTH OF THE COVER.
- R&G will accept no liability if the above procedure and torque settings are not followed.

R&G RACING

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



INSTRUCTIONS DE MONTAGE POUR ECC0118 (COTE DROIT)
PROTECTION CARTER MOTEUR
DUCATI DIAVEL



Ce kit contient:

- 1 x Protection carter moteur (ECC0118).
- 2 x M6x40mm Longs boulons à têtes rondes.
- 1 x M6x90mm Longs boulons à têtes rondes.
- 1 x M6x100mm Longs boulons à têtes rondes.

LIRE ATTENTIVEMENT LA NOTICE AVANT DE PROCEDER A L'INSTALLATION

- Veiller à ce que le moteur de la moto soit froid.
- Enlever les 4 boulons carter moteur comme indiqué ci-dessus. Appliquer à titre de repérage la protection autour du carter **UNIQUEMENT** pour identifier le placement des boulons.
- Installer la protection R&G Racing et placer le boulon le plus long (100mm) dans le trou indiqué par « B », le boulon légèrement plus court (90mm) dans le trou marqué par « A », et les boulons les plus courts (40mm) dans les 2 trous marqués « C ».
- A l'aide d'une clé Allen de 4mm, serrez les boulons de façon égale afin que la protection se mette en place de façon adaptée et naturelle. **NE PAS SERRER COMPLETEMENT.**
- Pour finir, utilisez une clé dynamométrique réglée à 10 nm (7 Lb ft) pour serrer complètement.

R&G RACING

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com



- Note importante:
-vérifier le serrage des vis au moins une fois par mois.
-Le nettoyage de la protection doit se faire à l'aide d'un produit nettoyant non agressif et à l'aide d'un chiffon doux.
Aucune garantie ne sera acceptée par R&G en cas de mauvais couple de serrage et en cas d'utilisation de nettoyeurs trop agressifs qui pourraient détériorer l'efficacité de la protection.

ISSUE 1 24/10/2011 (NSY)

CONSUMER NOTICE

The catalogue description and any exhibition of samples are only broad indications of the Products and R&G may make design changes which do not diminish their performance or visual appeal and supplying them in such state shall conform to the order. The Buyer acknowledges no representation or warranty (other than as to title) has been given or will apply to the Products other than those in R&G's order or confirmation and the Buyer confirms it has chosen the Products as being of merchantable quality and suitable for its particular purposes. Where R&G fits the Products or undertakes other services it shall exercise reasonable skill and care and rectify any fault free of charge unless the workmanship has been disturbed. The Buyer is responsible for ensuring that the warranty on the motorcycle is not affected by the fitting of the Products. On return of any defective Products R&G shall at its option either supply a replacement or refund the purchase money but shall not be liable if the Products have been modified or used or maintained otherwise than in accordance with R&G's or manufacturer's instructions and good engineering practice or if the defect arises from accident or neglect. Other than identified above and subject to R&G not limiting its liability for causing death and personal injury, it shall not be liable for indirect or consequential loss and otherwise its liability shall be limited to the amounts paid by the Buyer for the Products or the fitting or service concerned. These terms do not affect the Buyer's statutory rights.

R&G RACING RETURNS POLICY (NON-FAULTY GOODS)

Returns must be pre-authorized (if not pre-authorized the return will be rejected). Goods may only be returned direct to us if they were purchased direct from us (customer must prove if necessary). Otherwise to be returned to original vendor. Goods must be in re-sellable condition, in the opinion of R&G Racing. All returns are subject to a 25% restocking and handling fee (25% of the gross value exc. P&P – at the prevailing price at time of purchase). The customer must pay any and all carriage charges. No returns of discontinued products, unless within 14 days of purchase. This policy does not affect your statutory rights and does not refer to faulty goods.

R&G RACING

Unit 1 Shelleys Lane, East Worldham, Alton, Hants GU34 3AQ
Tel: +44 (0)1420 89007 Fax: +44 (0)1420 87301 www.rg-racing.com Email: info@rg-racing.com